

## Sizes and Options

Model: Multi-Use	Cubic Ft	Bushels	Overall Height	Min. Auger
MU1004	535	428	15.1'	27'
MU 1008	850	680	19.1'	33'
MU 1012	1164	931	23.1'	39'
MU 1208	1288	1030	20.8'	36'
MU 1210	1514	1211	22.8'	39'
MU 1212	1740	1392	24.8'	42'
MU 1410	1978	1582	24.1'	41'
MU 1415	2693	2155	29.1'	48'
MU 1420	3410	2727	34.1'	56'
MU 1425	4125	3300	39.1'	64'
MU 1430	4841	3872	44.1'	72'
MU 1610	2921	2337	26.2'	44'
MU 1615	3926	3141	31.2'	52'
MU 1620	4932	3945	36.2'	60'
MU 1625	5851	4749	41.2'	68'
MU 1630	6942	5554	46.2'	75'

### Accessories:

- 50, 55, 60 Degree Hoppers
- Aeration System
- Top Handrail
- Grain Gauge
- Probe Hole
- Skids



### Bottom Gate

Premium rack and pinion roller door allows easy opening and closing.



### Bracing

FCS has a unique "inverted-V" style bracing allowing plenty of room around the hopper.



### Top Door

Top door opens flat!



### Custom Color

If you have a specific color, we can match it!

## SMOOTHWALL BINS



**FCS Manufacturing, Inc.**

3430 EE Road | Gridley, Kansas 66852  
 Phone: 620-427-4200 | Fax: 620-427-4202  
 Email: info@fcsmf.com | www.fcsmf.com

**FCS Manufacturing Inc.**

# OUR STORY

Located in Southeastern Kansas, FCS Manufacturing is a family owned business, started over 30 years ago, with a reputation for building high-quality overhead grain storage for the agriculture industry.

In 2014, FCS was approached at a farm show about building round, smoothwall hopper-bottom bins, primarily for the wheat and soybean seed markets. After researching current products on the market and talking with seed dealers and ag producers, FCS developed a plan to provide a better product and better service.

This focus on solving industry needs led FCS to design and build a top-of-the-line product to store commodities that features heavy duty construction to stand up to high winds; a bright and durable painting process to keep a bright finish through years of sun and rain; and an innovative lid design with the industry's first snow-proof venting system.

### Why Smoothwall?

- interior smooth surface with no bolts or corrugations
- no more shoveling
- control your seed quality by storing in your own bins

# MULTI-USE



### Standard Features on Multi-Use (MU):

- 22" Ground Operated Top Door
- Snow proof Venting System
- Top and Side Ladder
- 16" R&P Bottom Gate
- Hopper Man access Hole
- 36" clearance under bottom gate
- Primed inside and outside with Enamel Top Coat
- 45 degree hopper slope



# FERTILIZER SERIES



All Fertilizer Series (FS) come with interior 2-part Epoxy Primer and Top Coat. This gives the inside an extremely hard and slick surface that will hold up to highly corrosive materials.